


## 产品型号IPC-5000H



## 产品特性

- ▶ Intel® 10th Gen Comet Lake-S Series with W480E
- ▶ Dual-channel DDR4 (ECC/non-ECC) 2933 MHz UDIMMs up to 128GB
- ▶ Triple independent displays: VGA, DP, HDMI, eDP
- ▶ 4 GbE LAN with RJ-45
- ▶ 1 PCIe x16 (Gen 3) or 2 PCIe x8 (Gen 3), 3 PCIe x4 (Gen 3), 2 PCI, 1 Mini-PCIe (Full/Half-size) slots
- ▶ 3 M.2 M key, 4 SATA 3.0 for storage
- ▶ SATA RAID 0/1/5/10
- ▶ 6\*USB 3.2 Gen 2 \*USB 2.0, 10 COM (2 RS-485), GPIO, LPT, PS/2, Audio, S/PDIF, 3 System FAN
- ▶ Onboard TPM 2.0
- ▶ SMBus, I2C, PMBus, iAMT 14.x, Chassis Intrusion
- ▶ ATX Power



 **技术参数**


■ 产品型号		IPC-5000H
系统	CPU	10th Gen Intel® Comet Lake-S Core™ i9/i7/i5/i3, Pentium®, Celeron® Processor, Max 125W
	芯片组	Intel® W480E Express
	系统内存	Dual-channel DDR4 (ECC/non-ECC) 2933 MHz
	扩展口	1 (Signal configured as 1 PCIe x16 or 2 PCIe x8) 3 (Slot 1 support Thunderbolt™ 3 card by request) pciex4 2 (pci)
	GPU&显卡	1*VGA up to 1920 x 1200 @60Hz 1*HDMI up to 4096 x 2160 @30Hz 1*DP up to 4096 x 2304 @60Hz
	音频	Realtek® ALC887-VD2-CG HD Audio Codec
	以太网	1 x Intel® I219-LM GbE LAN PHY 3 x Intel® I210-AT GbE LAN
	存储	3 x M.2 M key (PCIe x4 NVMe, signal shared with PCIe Slot 1 & 3 & 5), two with 2242/2260/2280, one with 2242/2260/2280/22110 4 x SATA 3.0 (RAID 0/1/5/10)
	PS/2	1 (wafer connector)
	USB接口	6 x USB 3.2 Gen 2 (6 x rear) 2 x USB 3.2 Gen 1 (2 x internal) 5 x USB 2.0 (2 x rear, 3 x internal with one Vertical Type-A Connector)
	串口接口	10 x COM ports (1 x rear, 9 x internal) COM1~2: RS-232/422/485, Ring/0V/5V/12V, Autoflow Control COM3~10: RS-232, 0V/5V/12V
	控制开关	1 * Power switch
	电源要求	ATX-Power 24P, 12V-8P
	GPIO	16-bits (8 x GPI; 8 x GPO), 5V
操作系统	Windows 10 IoT Enterprise 2019 SAC (64-bit, RS5) Linux Kernel 5.x (by request)	

结构	构造	SGCC箱体
	颜色	工业灰色
	安装方式	上架式安装
	尺寸	483x480x177mm
	净重	15KG
环境	工作温度	-10 ~ 60°C
	存储温度	-20 ~ 80°C
	存储湿度	10 ~ 90%, non-condensing
	振动	5grms/5~500Hz/随机/工作状态(SSD); 1grms/5~500Hz/随机/工作状态(HDD)
	冲击	50g峰值加速度(持续11ms)(SSD); 20g峰值加速度(持续11ms)(HDD)
	EMC/认证	CE/CCC

## ■ 订购信息

IPC-5000H	IPC-5000H/S001	I3-10100/2*LAN/6*USB3.2/2*USB2.0/1*RS232/1*VGA/1*DP/1*HDMI/ATX 24pin POWER
	IPC-5000H/S002	I5-10400/2*LAN/6*USB3.2/2*USB2.0/1*RS232/1*VGA/1*DP/1*HDMI/ATX 24pin POWER
	IPC-5000H/S003	I7-10700/2*LAN/6*USB3.2/2*USB2.0/1*RS232/1*VGA/1*DP/1*HDMI/ATX 24pin POWER
	IPC-5000H/S004	I9-10900/2*LAN/6*USB3.2/2*USB2.0/1*RS232/1*VGA/1*DP/1*HDMI/ATX 24pin POWER
供电	PA-250ATX	ADC110/220V宽范围，并且在DC90V~DC264V范围内正常工作
	PA-450ATX	ADC110/220V宽范围，并且在DC90V~DC264V范围内正常工作

## 外形尺寸



### 北京总部

公司电话: +86(0)10 -82331878/82331875

服务热线: 400-800-1871

办公地址: 北京市海淀区双清路3号鸿运大厦1层31078室

工厂地址: 河北省廊坊市三河市燕郊开发区留山大街

创智谷产业园-1#地块-一期-4#-2-101



了解更多信息: [www.ipccore.com](http://www.ipccore.com) ,或发送邮件到: [ipc@ipccore.com](mailto:ipc@ipccore.com)规格细节如有变更, 恕不另行通知

东方松柏科技(北京) 有限公司, 版权所有©2018